

Round Telescopic Packaging Tube with Ratchet Mechanism:

- telescopic length extension, ratchet mechanism locks in extended position
- square end prevents rolling
- rigid, durable, humidity and oil resistant
- speedy, efficient packing of products
- re-usable
- available with hanging loop

Availability:

- in transparent from stock
- please enquire for colours, clear and with hanging loop


Packing:

- outers and inners packed separately in individual cartons

Standard Material:

- Polypropylene (PP) transparent
- Polyethylene (PE) coloured

Note: Technical modification and availability subject to change without notice.



rose plastic UK Ltd.

Unit 4, Bessemer Way
Bessemer Business Park
Rotherham S60 1EN, England
Tel. ++44/1709/721794
Fax ++44/1709/724980
info@rose-plastic.co.uk
www.rose-plastic.co.uk

Ref.	ø mm	Length mm	Box Qty.
TP 7 050	7	050 - 090	3200
TP 7 075	7	075 - 115	2100
TP 9 040	9	040 - 065	2000
TP 9 065	9	075 - 110	2000
TP 12 050	12	050 - 080	2900
TP 12 080	12	080 - 120	3500
TP 12 120	12	120 - 200	2000
TP 12 200	12	200 - 360	2100
TP 14 050	14	050 - 080	2200
TP 14 080	14	080 - 120	2800
TP 14 120	14	120 - 200	1600
TP 14 200	14	200 - 360	1500
TP 16 050	16	050 - 080	1700
TP 16 080	16	080 - 120	2000
TP 16 120	16	120 - 200	1200
TP 16 200	16	200 - 360	1200
TP 18 050	18	050 - 080	1500
TP 18 080	18	080 - 120	1700
TP 18 120	18	120 - 200	1100
TP 18 200	18	200 - 360	1000
TP 20 050	20	050 - 080	1200
TP 20 080	20	080 - 120	1500
TP 20 120	20	120 - 200	1000
TP 20 200	20	200 - 360	900

Ref.	ø mm	Length mm	Box Qty.
TP 22 050	22	050 - 080	1000
TP 22 080	22	080 - 120	1300
TP 22 120	22	120 - 200	800
TP 22 200	22	200 - 360	750
TP 24 050	24	050 - 080	1900
TP 24 080	24	080 - 120	1200
TP 24 120	24	120 - 200	800
TP 24 200	24	200 - 360	650
TP 26 050	26	050 - 080	1700
TP 26 080	26	080 - 120	850
TP 26 120	26	120 - 200	550
TP 26 200	26	200 - 250	500
TP 28 050	28	050 - 080	1400
TP 28 080	28	080 - 120	800
TP 28 120	28	120 - 200	500
TP 28 200	28	200 - 360	450
TP 30 050	30	050 - 080	1200
TP 30 080	30	080 - 120	650
TP 30 120	30	120 - 200	400
TP 30 200	30	200 - 360	400
TP 32 050	32	050 - 080	1000
TP 32 080	32	080 - 120	650
TP 32 120	32	120 - 200	400
TP 32 200	32	200 - 360	350